



K21 is a single acting piston - rod seal and designed to have symmetrical lips in order to be used both for rod and piston applications.

PRODUCT ADVANTAGES

- Superior static and dynamic sealing effect
- Wide range of dimensions
- Easy assembly into closed grooves
- Simple groove design
- Economical sealing solution

APPLICATION

Construction machinery, fork-lift trucks, injection moulding machines, agricultural machinery, loading platforms and standard cylinders.

| MATERIAL | | CODE |
|----------|------------|--------|
| NBR | 90 SHORE A | NB9001 |
| PU | 92 SHORE A | PU9201 |

OPERATING CONDITIONS

| NBR | | | |
|--------------------|-----------------------------|----------------|----------------|
| MEDIA | Mineral oils (DIN 51524) | HFA and HFB | HFC |
| TEMPERATURE | -30°C +105°C | +5°C +60°C | -30°C +60°C |
| PRESSURE | ≤150 Bar | ≤150 Bar | ≤150 Bar |
| SPEED | ≤0.5 m/sec | ≤0.5 m/sec | ≤0.5 m/sec |
| PU | | | |
| MEDIA | Mineral oils (DIN 51524) | HFA and HFB | HFC |
| TEMPERATURE | -30°C +100°C | +5°C +50°C | -30°C +40°C |
| PRESSURE | ≤400 Bar | ≤400 Bar | ≤400 Bar |
| SPEED | ≤0.5 m/sec | ≤0.5 m/sec | ≤0.5 m/sec |

Note: The above data are maximum values and cannot be used at the same time.

| SURFACE ROUGHNESS | | Ra | Rmax |
|------------------------|-------------------------------------|--------------------|--------------------|
| Sliding Surface | $\varnothing D - \varnothing d$ | ≤0.4 μm | ≤3.2 μm |
| Groove Base | $\varnothing D_b - \varnothing d_p$ | ≤1.6 μm | ≤10 μm |
| Groove Flanks | B | ≤3.2 μm | ≤16 μm |

Note: It is recommended to have 50% to 90% of the working surface material contact area value.

INSTALLATION

Easily assembled into closed grooves according to the minimum diameter values that are given in the below table. Open grooves or special assembly tools should be used for the values that are outside this table. It is very important that the assembly tools must be of soft material and have no sharp edges. Before installation the seal must be oiled with system oil.

MINIMUM DIAMETER VALUES FOR CLOSED TYPE OF GROOVES

| | | | | | | | |
|-----------------|----|----|----|-----|----|------|-----|
| (D-d)/2 (mm) | 4 | 5 | 6 | 7.7 | 10 | 12.5 | 15 |
| dmin (mm) | 25 | 30 | 40 | 50 | 80 | 100 | 105 |

NOTES

For special applications that require high temperatures, K21 can be produced in FKM. The permissible sealing gap values of K21 piston - rod seal is given in the below table.

PERMISSIBLE SEALING GAP

| NBR | Smax (mm) | | |
|-----------|-----------|---------|---------|
| t=(D-d)/2 | 50 Bar | 100 Bar | 150 Bar |
| t≤5 | 0.40 | 0.20 | 0.10 |
| t>5 | 0.45 | 0.25 | 0.15 |
| PU | Smax (mm) | | |
| t=(D-d)/2 | 150 Bar | 250 Bar | 400 Bar |
| t≤5 | 0.30 | 0.20 | 0.15 |
| t>5 | 0.35 | 0.25 | 0.20 |

Note: The largest sealing gap value occurring on the non-pressurized side of the seal does have a vital importance for the function of the seal and in this respect it is quite important to use the S value lower than the above indicated numbers.